



# Decorative Vinyl & Fabric Corp.

Spec Sheet:

## Urban Exotics - Python

<http://dvcfabric.com/vinyl/product/python/>

Surface Type:	100% PVC		Date: 07/02/07
Weight at 54 inches:	31.5oz/yd		Revision: 0
Backing weight:	4.7oz/yd <sup>2</sup>		
Backing Type/composition:	100% Polyester		
Put-up:	30 yards		
Repeat:	6 1/2" V; 6" H		
Finish:	PVC		
Repeat:	None		
Cleaning Code:	W		
Railroaded:	N		
<b>Available Test</b>	<b>Values Required</b>	<b>Units</b>	<b>Test Method</b>
Finished Width	54"	In	CFFA-700a
Thickness	1.2±10%	mm	CFFA-700c
Total Weight	21.0±10%	Oz/yd <sup>2</sup>	CFFA-700d
Grab Tensile	85×75min	Lbs/in	CFFA-17
Trap Tear	20.0×20min	Lbs/in	CFFA-16c
Seam Strength	35×30min	Lbs/in	CFFA-14
Adhesion	3×3min	Lbs/in	CFFA-3
Flex Resistance	25,000	Cycles	CFFA-10
Blocking	No.1	Pass	CFFA-4
Wyzenbeek Abrasion	Pass - 30,000	Cycles	CFFA-1a
		Wire screen	
UV Stability	40 indoor hours	No colour change	QUV
Crock Resistance	20 - no stain	Cycles	CFFA-7
Stretch (MD×CD)	8%×18%	% at 15#	CFFA-17
<b>Flame Resistance:</b>			
California Technical Bulletin 117, Section E.		Meets Requirements	
U.F.A.C. Class I		Meets Requirements	
NFPA 260		Meets Requirements	
May comply with California 133 when tested with suitable components.			
<b>Country of Origin: China</b>			