



Decorative Vinyl & Fabric Corp.

Spec Sheet:

Urban Exotics - Venice

<http://dvcfabric.com/vinyl/product/venice/>

Technical Specs

	<u>Values</u>	<u>Test Method</u>
Surface Composition	100% PU	
Finished Width	54" min.	ASTM D 751-06
Weight at 54 inches	30 oz/yd	ASTM D 751-06
Thickness	1.25 mm ±10%	ASTM D 751-06
Total Weight	20 oz./yd ² ±10%	ASTM D 751-06
Backing Composition	65% Polyester / 35% Cotton	ASTM D 751-06
Backing Weight	8.0 oz / sq. yd ²	ASTM D 751-06
Repeat	None	
Railroaded	No	
Put-up	30 yards	
Cleaning Code	W	

Performance

	<u>Values</u>	<u>Test Method</u>
Grab Tensile	100 lbs./in. × 100 lbs./in. min.	ASTM D 751-06
Trap Tear	20 lbs./in. × 18lbs./in. min.	ASTM D 751-06
Seam Strength	90 lbs./in. × 90 lbs./in. min.	ASTM D 751-06
Adhesion	5 lbs./in. × 5 lbs./in. min.	ASTM D 751-06
Stretch @ 15# (MD×CD)	4% × 7%	ASTM D 751-06
Flex Resistance	25,000 Cycles	ASTM D 2097-03(2010)
Blocking	No. 1 - Pass	FTMS 191A-TM5872
Crock Resistance	20 cycles - Pass	AATCC 8-2007
Wyzenbeek Abrasion	Pass - 100,000 cycles, #8 cotton duck	ASTM D 4157-92
UV Stability	40 hours (no color change)	ASTM D 4329-05

Flammability

	<u>Values</u>
California Bulletin 117, Section E.	Pass
U.F.A.C. Class I	Pass
NFPA 260	Pass

Suitable Applications: Commercial

Country of Origin: China

08/15/2009 - Revision: 1