

Decorative Vinyl & Fabric Corp. Spec Sheet:

Omnova - Weave

http://dvcfabric.com/vinyl/product/weave/

Description: Weave micro-weave pattern withhorizontal striations for a unique organic appearance. Features PreFixx® protective finish for outstanding stain, abrasion and chemical resistance allowing it to be repeatedly cleaned and disinfected with a wide variety of chemicals without worrying about discoloration or damage to the upholstery finish.

Use: Both Interior and Exterior

Width: 54"

Total Weight: 28 ounces/linear yard Backing Weight 3.7 ounces/linear yard

Backing: Terry loop knit

Backing Composition: Polyester

Construction: Expanded Composition: Vinyl

Protective Coating: PreFixx®

Roll Size: 40 yards

Surface Finish: Light emboss

SPECIFICATIONS

FMVSS302 Specification Compliant: Yes

UV Stability - CFFA2 (UVA 340 bulb): 650 Hours outdoors

Flammability Specifications: California Technical Bulletin 117-75, Sec. E

Federal Specification CID A-A-2950 superseding CCC-A-680A

NFPA 701 FMVSS-302 FAA-FAR25.853 Boston IX-1

UFAC Fabric, Class 1

Tack Strength - CCFA 14: 35 x 30

Tensile Strength: 85 x 75 Adhesion - CFFA 3: 4.0# Min. Shipping Weight: 68 lbs/roll

Wyzenbeek Abrasion - CFFA 1: 60,000 cycles stainless steel screen wire

1.3 million cycles #8 cotton duck

Due to possible variances in your computer monitor, the colors and patterns displayed may vary slightly from the actual product.

Customers should always obtain and compare actual samples before specifying.