



Decorative Vinyl & Fabric Corp.

PRODUCT SPECIFICATION

ANU LEATHER CANYON

Surface Type:	100% PU		05/11/09
Weight at 54 inches:	15oz/yd		Revision: 0
Backing weight:	5.3oz/yd ²		
Backing Type/composition:	100% Rayon		
Put-up:	35 yards		
Repeat:	None		
Finish:	Urethane Finish		
Cleaning Code:	W		
Railroaded:	N		
Available Test	Values Required	Units	Test Method
Finished Width	54" min	In	CFFA-700a
Thickness	0.8±10%	mm	CFFA-700c
Total Weight	10±10%	Oz/yd ²	CFFA-700d
Grab Tensile	70×60min	Lbs/in	CFFA-17
Trap Tear	15×12min	Lbs/in	CFFA-16c
Seam Strength	50×50min	Lbs/in	CFFA-14
Adhesion	4×4min	Lbs/in	CFFA-3
Flex Resistance	25,000	Cycles	CFFA-10
Blocking	No.1	Pass	CFFA-4
Wyzeenbeek Abrasion	50,000	Cycles Wire Screen	Federal Standard 191A Method 5304
Hydrolysis Resistance	No delaminating	Visual	6 hours boiling water
UV Stability	40 indoor hours	No colour change	QUV
Crock Resistance	20 - no stain	Cycles	CFFA-7
Stretch (MD×CD)	2×18	% at 15#	CFFA-17
Flame Resistance:			
California Technical Bulletin 117, Section E.		Meets Requirements	
U.F.A.C. Class I		Meets Requirements	
NFPA 260		Meets Requirements	
IMO A.652(16)8.2 & 8.3		Meets Requirements	
May comply with California 133 when tested with suitable components.			
Country of Origin: China			

DVC Fabric
 4527 GLENWOOD ROAD
 BROOKLYN, NY 11203
 P: 718 941 3326
 F: 718 941 6115
 E: sol@dvcfabric.com