



Decorative Vinyl & Fabric Corp.

## PRODUCT SPECIFICATION

### EVERGLADE

Product Type:	100% PVC		Date: 9/20/06
Weight at 54 inches:	33oz/yd		Revision: 1
Backing weight:	3.5oz/yd <sup>2</sup>		
Backing Type/composition:	P/C: 65%:35%		
Put-up:	30 yards		
Repeat:	8" H; 4" V		
<b>Available Test</b>	<b>Values Required</b>	<b>Units</b>	<b>Test Method</b>
Finished Width	54"	In	CFFA-700a
Thickness	1.0±10%	mm	CFFA-700c
Total Weight	22.0±10%	Oz/yd <sup>2</sup>	CFFA-700d
Grab Tensile	80.0×80.0min	Lbs/in	CFFA-17
Trap Tear	18.0×18.0min	Lbs/in	CFFA-16c
Seam Strength	75.0×65.0min	Lbs/in	CFFA-14
Adhesion	4.0×4.0min	Lbs/in	CFFA-3
Flex Resistance	25,000	Cycles	CFFA-10
Blocking	No.1	Grade	CFFA-4
Wyzenbeek Abrasion	Pass - 35,000	Cycles #8 Cotton Duck	Federal Standard 191A Method 5304
UV Stability	40 indoor hours	No colour change	QUV
Crock Resistance	20 - no stain	Cycles	CFFA-7
Stretch (MD×CD)	2%×7%	% at 15#	CFFA-17
<b>Flame Resistance:</b>			
California Technical Bulletin 117, Section E.		Meets Requirements	
U.F.A.C. Class I		Meets Requirements	
NFPA 260		Meets Requirements	
May comply with California 133 when tested with suitable components.			
<b>Country of Origin: China</b>			

DVC Fabric

4527 GLENWOOD ROAD

BROOKLYN, NY 11203

P: 718 941 3326

F: 718 941 6115

E: sol@dvcfabric.com