

Amarillo

SPECIFICATIONS

Description	Amarillo 1016 Canyon
Abrasion	Exceeds 200,000 Double Rubs.
Backing Content	35% Cotton 65% Polyester
Cleaning Instruction	See Features/Cautions.
Cold Crack	Product Cold Crack is equal to or greater than -40 degrees Celsius (-40 Fahrenheit)
Colors Available	10 colors available.
Content	100% Polyurethane (PU)
Description	Engineered Leather
Features	Wipe with a soft cloth, with cold water and a mild soap. Dry immediately. Maintain with Leather Protectant. DO NOT IRON
Fire Retardancy	California Bulletin 117-Section E, Motor Vehicle Safety Standard 302. NFPA 260 Class 1.
Roll Size	40 yards (36.5 m)
Tear Strength	Passes ASTM D2261 - Warp = 21 lbs and Fill = 12 lbs.
Ultraviolet	Colorfastness to Light AATCC16 Class 4.5
Weight	13.62 ounces per square yard. 20.44 Ounces per Linear Yard
Width	54" (137 cm)

** This information is offered for your general guidance only. It is accurate to the best of our knowledge and is not intended to relieve the user from its responsibility to investigate and understand other pertinent sources of information and to comply with all laws and procedures applicable to the safe handling and use of this material. Final determination of the suitability of any product for an application rests with the user.

*This term and any corresponding data refer to typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Although we do our best to make sure that the colors on our web site are accurate, actual colors will vary. Subtle color differences and textures may not be fully appreciated on some systems due to differences in monitors and/or printers.