



Decorative Vinyl & Fabric Corp.

Spec Sheet:

Contract Fabrics

<http://dvcfabric.com/vinyl/product/heavenly/>

Description Heavenly

Abrasion Exceeds 125,000 Double Rubs.

Backing Content 100% Acrylic

Cautions Cleaning Instructions - Use Mild Detergent

Cleaning Instruction Machine Wash with Care

Colors Available 33 colors available.

Construction Chenille Woven

Content 100% Polyester

Fire Retardancy California Bulletin 117-Section E, UFAC Class 1

Pilling Passes ASTM D3511 - Class 4.5

Railroaded Pattern Non-Directional

Roll Size 50 yards (45.7 m)

Seam Slippage Passes Seam Slippage ASTM D434. W 64 x F 70 LBF

Style Solids / Plain Texture

Tear Strength Passes ASTM D2261 - Warp = 36 lbs and Fill = 24 lbs.

Tensile Strength Passes ASTM D5034 - Warp = 335 lbs and Fill = 168 lbs.

Ultraviolet Colorfastness to Light

Uses Upholstery

Weight 13.34 Ounces per Linear Yard 8.73 ounces per square yard.

Width 55" (140.0 cm)

**** This information is offered for your general guidance only. It is accurate to the best of our knowledge and is not intended to relieve the user from its responsibility to investigate and understand other pertinent sources of information and to comply with all laws and procedures applicable to the safe handling and use of this material. Final determination of the suitability of any product for an application rests with the user.**

***This term and any corresponding data refer to typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.**

Although we do our best to make sure that the colors on our web site are accurate, actual colors will vary. Subtle color differences and textures may not be fully appreciated on some systems due to differences in monitors and/or printers.