



Decorative Vinyl & Fabric Corp.

Spec Sheet:

Contract Fabric - Venue TFL

<http://dvcfabric.com/vinyl/product/venue-tfl/>

Specifications

- content: 100% Polyester
- backing: Fleece Bonding
- finish: Teflon
- weight: 22.4 oz / lin. yd. (777g/M)
- width: 54"

Performance

- abrasion:
- 80,000 Cycles
-
- light fastness:
- Class 4/40 hrs. min. (AATCC16A)
-
- color fastness:
- Class 3 (ASTM D3597, AATCC 8) Wet
- Class 4 (ASTM D3597, AATCC 8) Dry
-
- physical properties:
- Class 4 (ASTM D3511) Brush Pill
- 84 warp, 66 lbs. weft (ASTM D4034) Breaking Strength
- 12 warp, 11 lbs. weft (ATSM D2261-96) Tear Strength
- 65 warp, 49 lbs. weft (ASTM D4034) Seam Slippage

Flammability

- passes:
- California Tech. Bulletin #117 Section E (CS-191-53)
- UFAC Class 1
- NFPA 260 Class 1

Care

- cleanability:
- W – Water based cleaners may be used

Pattern images shown up the roll.

Due to pattern scale and color variations in computer monitors and printers, we strongly suggest you view actual samples before making a selection.