



Decorative Vinyl & Fabric Corp.

Spec Sheet:

Contract Fabric - Winslow

<http://dvcfabric.com/vinyl/product/winslow/>

Specifications

- content: 100% Polyester
- backing: Acrylic
- repeat: 15 in. / horizontal: 5 in. / vertical
- weight: 11.2 oz / lin. yd. (417g/M)
- width: 54"

Performance

- abrasion:
 - Heavy Duty – 40,000 Cycles
 - (Wyzenbeek – Cotton duck Abradant) (ASTM D4157)
 -
- light fastness:
 - Class 4/40 hrs. min. (AATCC16A)
 -
- color fastness:
 - Class 4 (ASTM D3597, AATCC 8) Wet
 - Class 4 (ASTM D3597, AATCC 8) Dry
 -
- physical properties:
 - Class 4 (ASTM D3511) Brush Pill
 - 106 warp, 87 lbs. weft (ASTM D4034) Breaking Strength
 - 15 warp, 28 lbs weft (ASTM D2262) Tear Strength
 - 74 warp, 49 lbs. weft (ASTM D4034) Seam Slippage

Flammability

- passes:
 - California Tech. Bulletin #117 Section E (CS-191-53)
 - UFAC Class 1
 - NFPA 260

Care

- cleanability:
 - W – Water based cleaners may be used

Pattern images shown up the roll.

Due to pattern scale and color variations in computer monitors and printers, we strongly suggest you view actual samples before making a selection.