



Decorative Vinyl & Fabric Corp.

<http://dvcfabric.com>

4527 GLENWOOD ROAD
BROOKLYN, NY 11203
P: 718 941 3326
F: 718 941 6115
E: sol@dvcfabric.com

Pattern: Imperial 600

Product Specification Sheet

Imperial Brand Fabrics

General Specifications

Weight (linear yard)	24.0 oz
Width	58 "
Thickness	0.62 mm
Gauge	N/A
Emboss	Taffeta
Surface Composition	100 % Polyester
Substrate Composition	PVC 600 x 300D
Substrate Thread Count	35 x 33

General Treatments

UV Resistance CFFA-2 / ASTM G26-96 Method C	0 Hours
Cold Crack CFFA-6 Federal Standard No. 191A-Method 5874	-10 F
Mildew Resistant CFFA-120 / ASTM G21-96	N/A
Anti-Bacterial / Anti-Microbial CFFA-300 / AATCC* Test Method 147-1998	N/A
Resilience ^{SR}	N/A
Bleach Resistant (diluted 1:10)	N/A

Physical Strength Properties

Abrasion CFFA-1A/ Method ASTM D 4157-92	1000 Cycles
Adhesion CFFA 3 / ASTM D751-98	N/A Warp N/A Fill
Tear Strength by Tongue ASTM D 2261-07	12.7 Warp 24.4 Fill
Break Strength FTM 5100.1	314.1 Warp 372.2 Fill
Pendulum Test Method ASTM D 751, SECTION 22-28	N/A Warp N/A Fill
Flex Resistance of Finish CFFA-10/ASTM D2097-03(2005)	25,000 Warp 25,000 Fill

Flame Retardancy Standards

California Technical Bulletin 117	Pass
UFAC Class I	N/A
BIFMA CS-191-53, Section 3	N/A
BIFMA Upholstery, Section 4	N/A
MVSS 302	N/A
NFPA 260	N/A
Boston Fire Code (BFD IX-1)	N/A
IMO A.652(16)8.2	N/A
ASTM E84: Class I or A Rating	N/A

** CAL 133 (when used with suitable components)

*** Can be treated to pass FAR 25.853