

Decorative Vinyl & Fabric Corp. Spec Sheet:

Atelier Impressed Metallic - Analog http://dvcfabric.com/vinyl/product/analog/

Application

Upholstery

Contents

Surface - 100% Polyurethane with exclusive Graffiti-Free [®] layer

Back - 100% Pollex™

Width

53/54"

Nominal Thickness

36/38 gauge

Repeat

App. 6.6" H, 7" V

Roll Length

App. 40yds

General Characteristics

Superior wear resistance: Exceeds 100,000 rubs (ASTM D4157

Wyzenbeek)

Hydrolysis Resistance: 10+ weeks

- ISO1419:1995, Method C, Tropical Test

Anti-bacterial/Anti-microbial (AATCC-147)

Colorfastness to light (AATCC-16/passes)

Colorfastness to crocking (AATCC-8/passes)

Colorfastness to bleach (AATCC-3): passes 1:10 & 1:5 dilution test

Excellent breaking strength (ASTM D5034)

Excellent tear strength (ASTM D2262)

Cold crack resistant & mildew resistant backing

Flammability

CAL-117, UFAC/NFPA-260

IMO A652 (16) 8.2

Care & Cleaning

Exclusive Graffiti-Free * protection for easy care, stain-free surface

- 1. Most stains and ballpoint pen marks* can be easily wiped away with a clean dry towel.** No need to use complicated cleaning procedures.
- 2. Spot clean the spilled area with mild soap and water.
- 3. Rubbing alcohol (isopropyl alcohol)*** can be used to clean any remaining stain. Rinse the cleaned area with clean water and dry with air or lint-free cloth.
- + Always test on an inconspicuous area first.

Disinfectability

This item is formulated to achieve a superior level of disinfectability with a 5:1 bleach solution.

Warranty

Please refer to our Terms of Sales for warranty information.

- *Graffiti-Free ® does not protect the product against intentional stains.
- **Use non-abrasive soft cloth/napkin to avoid scratching of the surface.
- ***Caution: Exercise care as alcohols are flammable. Use only small amount and keep clear of any source of ignition. Wear protective gloves during cleaning activities.

4527 GLENWOOD ROAD BROOKLYN, NY 11203 P: 718 941 3326 F: 718 941 6115 E: sol@dvcfabric.com