



Decorative Vinyl & Fabric Corp.

Spec Sheet:

Atelier Impressed Metallic - Axis

<http://dvcfabric.com/vinyl/product/axis/>

Application

Upholstery

Contents

Surface - 100% Polyurethane with exclusive Graffiti-Free[®] layer

Back - 100% Pollex[™]

Width

53/54"

Nominal Thickness

36/38 gauge

Repeat

App. 4.375" H, 3.375" V

Roll Length

App. 40yds

General Characteristics

Superior wear resistance : Exceeds 100,000 rubs (ASTM D4157 Wyzenbeek)

Hydrolysis Resistance : 10+ weeks

- ISO1419:1995, Method C, Tropical Test

Anti-bacterial/Anti-microbial (AATCC-147)

Colorfastness to light (AATCC-16/passes)

Colorfastness to crocking (AATCC-8/passes)

Colorfastness to bleach (AATCC-3) : passes 1 :10 & 1:5 dilution test

Excellent breaking strength (ASTM D5034)

Excellent tear strength (ASTM D2262)

Cold crack resistant & mildew resistant backing

Flammability

CAL-117, UFAC/NFPA-260

IMO A652 (16) 8.2

Care & Cleaning

Exclusive Graffiti-Free[®] protection for easy care, stain-free surface

1. Most stains and ballpoint pen marks* can be easily wiped away with a clean dry towel.** No need to use complicated cleaning procedures.

2. Spot clean the spilled area with mild soap and water.

3. Rubbing alcohol (isopropyl alcohol)*** can be used to clean any remaining stain. Rinse the cleaned area with clean water and dry with air or lint-free cloth.

+ Always test on an inconspicuous area first.

Disinfectability

This item is formulated to achieve a superior level of disinfectability with a 5:1 bleach solution.

Warranty

Please refer to our Terms of Sales for warranty information.

*Graffiti-Free[®] does not protect the product against intentional stains.

**Use non-abrasive soft cloth/napkin to avoid scratching of the surface.

***Caution: Exercise care as alcohols are flammable. Use only small amount and keep clear of any source of ignition. Wear protective gloves during cleaning activities.

4527 GLENWOOD ROAD

BROOKLYN, NY 11203

P: 718 941 3326

F: 718 941 6115

E: sol@dvcfabric.com