



Decorative Vinyl & Fabric Corp.

Spec Sheet:

Premium Tex - New Wave - Chariot

<http://dvcfabric.com/vinyl/product/chariot/>

Application

Upholstery

Contents

Surface - Phthalate Free Vinyl with exclusive Graffiti-Free[®] layer

Back - 65% Polyester / 35% Cotton

Width

54"

Nominal Thickness

44/48 gauge

Nominal Weight

30 oz. / linear yard

Repeat

App. 22.375" H / 10.25" V

Roll Length

App. 40yds

General Characteristics

Phthalate Free Construction

Superior wear resistance : Exceeds 100,000 rubs (ASTM D4157

Wyzenbeek)

Colorfastness to light (AATCC-16/passes)

Colorfastness to crocking (AATCC-8/passes)

Colorfastness to bleach (AATCC-3) : passes 1:10 & 1:5 dilution test

Resistance to various stains (MS 300-32 4.21)

- Oil, Grease, Nicotine, Tar, Mud, etc.

Flammability

CA Bulletin 117-2013, UFAC/NFPA-260

IMO A652 (16) 8.2

Care & Cleaning***

Exclusive Graffiti-Free[®] protection for easy care, stain-free surface

1. Most stains and ballpoint pen marks* can be easily wiped away with a clean dry towel.** No need to use complicated cleaning procedures.

2. Spot clean the spilled area with mild soap and water.

3. Rubbing alcohol (isopropyl alcohol) can be used to clean any remaining stain. Rinse the cleaned area with clean water and dry with air or lint-free cloth.

+ All stains and spills should be addressed immediately. The longer it remains, the more difficult it will be to remove.

+ Always test on an inconspicuous area first.

Disinfectability

This item is formulated to achieve a superior level of disinfectability with a 5:1 bleach solution.

Warranty

Please refer to our Terms of Sales for warranty information.

4527 GLENWOOD ROAD

BROOKLYN, NY 11203

P: 718 941 3326

F: 718 941 6115

E: sol@dvcfabric.com