



Decorative Vinyl & Fabric Corp.

Spec Sheet:

Skintex - Glamour

<http://dvcfabric.com/vinyl/product/glamour/>

Application

Upholstery

Contents

Surface - 100% Polyurethane

Back - 100% Polyester

Width

54"

Nominal Thickness

36/38 gauge

Nominal Weight

16 oz. / linear yard

Repeat

App. 1.5" H, 1.5" V

Roll Length

App. 50yds

General Characteristics

Superior wear resistance : Exceeds 100,000 rubs (ASTM D4157 Wyzenbeek)

Hydrolysis Resistance : 10+ weeks

- ISO1419:1995, Method C, Tropical Test

Colorfastness to light (AATCC-16/passes)

Colorfastness to crocking (AATCC-8/passes)

Colorfastness to bleach (AATCC-3) : passes 1 :10 & 1:5 dilution test

Excellent breaking strength (ASTM D5034)

Excellent tear strength (ASTM D2262)

Cold crack resistant & mildew resistant backing

Flammability

CAL-117, UFAC/NFPA-260

IMO A652 (16) 8.2

Care & Cleaning

Cleaning Code : S/W

Stain Removal : Spot cleaning with mild soap and water will remove most of the everyday stains. Tough, difficult stains can be cleaned with alcohol-based solutions followed by clean water rinse.

+ All stains and spills should be addressed immediately. The longer it remains, the more difficult it will be to remove.

+ Always test on an inconspicuous area first.

Disinfectability

This item is formulated to achieve a superior level of disinfectability with a 5:1 bleach solution.

Options

Graffiti-Free[®] finish for stain free environment

Warranty

Please refer to our Terms of Sales for warranty information.

4527 GLENWOOD ROAD

BROOKLYN, NY 11203

P: 718 941 3326

F: 718 941 6115

E: sol@dvcfabric.com