



Decorative Vinyl & Fabric Corp.

Spec Sheet:

Skintex SF - Pop

<http://dvcfabric.com/vinyl/product/pop/>

Application

Upholstery

Contents

Surface - 100% Polyurethane with exclusive Graffiti-Free[®] layer

Back - 100% Polyester

Width

54"

Nominal Thickness

36/38 gauge

Repeat

N/A

Roll Length

App. 50yds

General Characteristics

Superior wear resistance : Exceeds 200,000 rubs (ASTM D4157 Wyzenbeek)

Hydrolysis Resistance : 10+ weeks

- ISO1419:1995, Method C, Tropical Test

Colorfastness to light (AATCC-16/passes)

Colorfastness to crocking (AATCC-8/passes)

Colorfastness to bleach (AATCC-3) : passes 1:10 & 1:5 dilution test

Excellent breaking strength (ASTM D5034)

Excellent tear strength (ASTM D2262)

Cold crack resistant & mildew resistant backing

Flammability

CA Bulletin 117-2013, UFAC/NFPA-260

IMO A652 (16) 8.2

Care & Cleaning

Exclusive Graffiti-Free[®] protection for easy care, stain-free surface

1. Most stains and ballpoint pen marks* can be easily wiped away with a clean dry towel.** No need to use complicated cleaning procedures.

2. Spot clean the spilled area with mild soap and water.

3. Rubbing alcohol (isopropyl alcohol) can be used to clean any remaining stain. Rinse the cleaned area with clean water and dry with air or lint-free cloth.

+ All stains and spills should be addressed immediately. The longer it remains, the more difficult it will be to remove.

+ Always test on an inconspicuous area first.

Disinfectability

This item is formulated to achieve a superior level of disinfectability with a 5:1 bleach solution.

Warranty

Please refer to our Terms of Sales for warranty information.

4527 GLENWOOD ROAD

BROOKLYN, NY 11203

P: 718 941 3326

F: 718 941 6115

E: sol@dvcfabric.com