



Decorative Vinyl & Fabric Corp.

Spec Sheet:

Texsuede - Soave

<http://dvcfabric.com/vinyl/product/soave/>

Application

Upholstery

Contents

80% Polyester, 15% Cotton, 5% Polyurethane

Width

55/56"

Nominal Weight

9 oz. / square yard

Repeat

N/A

Roll Length

App. 50yds

General Characteristics

Superior wear resistance : Exceeds 100,000 rubs (ASTM D4157 Wyzenbeek)

Colorfastness to light (AATCC-16/passes)

Colorfastness to crocking (AATCC-8/passes)

Tensile strength (ASTM D5034)

Tear strength (ASTM D1424)

Seam Slippage (ASTM D4034)

Flammability

CAL-117, UFAC/NFPA-260

Care & Cleaning

Cleaning Code : W (Water Based Cleaners)

General Care : Texuede SP contains built-in stain resistant system. Liquid stains and spills will remain on the surface temporarily, but should be cleaned as soon as possible.

Stain Removal : Spot clean with mild soap and warm water solution. Rinse the cleaned area with clean/clear water and dry with air or lint-free cloth.

Warranty

Please refer to our Terms of Sales for warranty information.

4527 GLENWOOD ROAD

BROOKLYN, NY 11203

P: 718 941 3326

F: 718 941 6115

E: sol@dvcfabric.com