


Pattern Detail and Specifications

Bravo		Specifications:
		content: 88% polyester, 12% Polyurethane
		backing: 100% Polyester
		finish: none
		repeat: n/a
weight: 11.68 oz / lin. yd.		
width: 54 inches		

Flammability Passes:

California Tech. Bulletin #117-2013
UFAC Class 1
NFPA 260 Class 1

Performance:

abrasion: Heavy Duty – Exceeds 100,000 Cycles
(Wyzenbeek – #10 Cotton duck Abradant) (ASTM D 4157)

light fastness: Class 4/40 hrs. min. (AATCC16A)

color fastness: Class 4.5 (ASTM D3597, AATCC 8) Wet
Class 4.5 (ASTM D3597, AATCC 8) Dry

physical properties: Class 4 (ASTM D3511) Brush Pill
158 warp, 84 lbs. weft (ASTM D4034) Breaking Strength
68 warp, 54 lbs. weft (ASTM D4034) Seam Slippage

made in: China

Care & Cleanability:

Cleaning code **W** - Spot clean only with water based upholstery shampoo or foam upholstery cleaner. Pretest a small, inconspicuous area before proceeding. Do not over wet. Do not use solvents to spot clean. Cushion covers should not be removed and laundered. When cleaning a spill, blot immediately to remove the spilled material. Evenly clean the entire panel in a seam to seam fashion. Do not clean just the spots or stains. When an overall soiled condition has been reached and professional care is required, contact an IICRC certified firm (www.iicrc.org).