Decorative Vinyl & Fabric

Pattern Detail and Specifications

Linette

Specifications:

content:	100% Vinyl
backing:	100% Polyester
finish:	Antimicrobial, i-clean
Repeat:	n/a
weight:	40.19 oz. per yard
width:	54 inches

Flammability Passes:

California Tech. Bulletin #117-2013
UFAC Class 1
NFPA 260 Class 1

MVSS 302

Performance:

abrasion:	Heavy Duty – Exceeds 100,000 cycles
	(Wyzenbeek – Wire screen abradant) (ASTM D4157)
light fastness:	Class 4/200 hrs. min. (AATCC16A)
color fastness:	Class 5 (ASTM D3597, AATCC 8) Wet
	Class 5 (ASTM D3597, AATCC 8) Dry
physical properties:	Class 5 (ASTM D3511) Brush Pill
	137 lbs. warp, 143 lbs. weft (ASTM D5034) Breaking Strength
	88 lbs. warp, 94 lbs. weft (ASTM D4034) Seam Slippage
	50,000 cycles (CFFA 10) Flex Resistance
	Pass (CFFA 6a) Cold Crack
environmental benefits:	
made in:	China

Care & Cleanability:

A clean cloth, dampened with the appropriate cleaning solution, should be applied to the affected areas as soon as possible. Blot the fabric with the treated cloth, working from the outer edge of the stained area and moving in toward the center. In order to effectively draw out the stain, renew the cleaning cloth as often as necessary to maintain an absorbent surface.

Clean all stained areas as soon as possible in accordance with the recommended stain removal procedures. Spot clean with upholstery shampoo, foam from a mild detergent, or mild dry
eaning is not a recommended cleaning
the middle of the affected area to prevent
circling (see Stain Removal Matrix below).