

Guardian Specs

Content

Vinyl | Urethane Topcoat

Backing

Hi-Loft²™

Finish

PBG+® PERMABLOK³®
PERMAGUARD®

Ag SILVERGUARD®
SILVER ION TECHNOLOGY

Characteristics

Antibacterial
Antifungal
Mildew Resistant
Stain Resistant
No Heavy Metals
Formaldehyde Free

Performance

Superior Abrasion
CFFA 1-a, ASTM D-4157
100,000 cycles, Wyzenbeek #10 Cotton Duck

Cold Crack -10°F
CFFA 6-a

UV Stabilized Pigments
Xenotest: AATCC Blue Wool
1,000 hours
QUV: ASTM D-4329 / CFFA-2 c2 - Grey Scale
650 hours



This fabric meets or exceeds these
ACT performance guidelines.
*Certification Marks owned by ACT®

Flame Retardancy*

California T.B. 117 - 2013
FMVSS 302
IMO FTP 2010
Code MSC.307(88), Part 8, 3.1 & 3.2
NFPA 260 - Class I
UFAC - Class I
Boston Fire Code
Federal Aviation Specification
Federal ST. 191A M 5903.1
Port Authorities of NY & NJ

*This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

All Spradling International's vinyl- and PU- coated fabrics contain flame retardant additives.

Specifics

Weight: 30 oz.
Width: 54 in.
Roll Size: 30 yd.

Applications

Corporate
Restaurant
Hospitality
Sunroom
Marine Interiors
Auto | RV
Residential Interiors