

### Hitch Specs

#### Content

Vinyl | Urethane Topcoat

#### Backing

Hi-Loft<sup>2</sup>™

#### Finish

**PERMABLOK<sup>3</sup>®**



#### Characteristics

Antibacterial  
Antifungal  
Mildew Resistant  
Stain Resistant  
No Heavy Metals  
Formaldehyde Free

#### Performance

Superior Abrasion  
CFFA 1-a, ASTM D-4157  
75,000 cycles, Wyzenbeek #10 Cotton Duck

Cold Crack -10°F  
CFFA 6-a

UV Stabilized Pigments  
Xenotest: AATCC Blue Wool  
1,000 hours  
QUV: ASTM D-4329 / CFFA-2 c2 - Grey Scale  
650 hours



This fabric meets or exceeds these  
ACT performance guidelines.  
\*Certification Marks owned by ACT®

#### Flame Retardancy\*

California T.B. 117 - 2013  
FMVSS 302  
IMO FTP 2010  
Code MSC.307(88), Part 8, 3.1 & 3.2  
NFPA 260 - Class I  
UFAC - Class I

\*This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

All Spradling International's vinyl- and PU- coated fabrics contain flame retardant additives.

#### Specifics

Weight: 27 oz.  
Width: 54 in.  
Roll Size: 30 yd.

#### Applications

Corporate  
Restaurant  
Hospitality  
Sunroom  
Marine  
Auto | RV  
Residential Interiors | Exteriors