Decorative Vinyl & Fabric

Reflex Specs

Content
Vinyl | Urethane Topcoat

Backing
Hi-Loft2™

Finish
PERMABLOK3®

Ag SILVERGUARD®
SILVER ION TECHNOLOGY

Characteristics
Antibacterial

Antifungal

Stain Resistant

No Heavy Metals

Formaldehyde Free

Performance
Superior Abrasion
CFFA 1-a, ASTM D-4157
100,000 cycles, Wyzenbeek #10 Cotton Duck

Cold Crack -20°F
CFFA 6-a

UV Stabilized Pigments
Xenotest: AATCC Blue Wool
1,000 hours

A *

This fabric meets or exceeds these ACT performance guidelines.
*Certification Marks owned by ACT®

Flame Retardancy*
California T.B. 117 - 2013

FMVSS 302

IMO FTP 2010
Code MSC.307(88), Part 8, 3.1 & 3.2

NFPA 260 - Class I

UFAC - Class 1

Boston Fire Code

Federal Aviation Specification

Federal ST. 191A M 5903.1

Port Authorities of NY & NJ

*This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

All Spradling International's vinyl- and PU- coated fabrics contain flame retardant additives.

Specifics
Weight: 30 oz.

Width: 54 in.

Roll Size: 30 yd.

Applications
Auto | RV

Residential Interiors

4/15/16

DVC Fabric 4527 GLENWOOD ROAD BROOKLYN, NY 11203 P: 718 941 3326 F: 718 941 6115 E: sol@dvcfabric.com