DVC
Decorative Vinyl & Fabric

Sphere Specs

Content
Vinyl | Urethane Topcoat

Backing
Hi-Loft^{2}™

Finish
PERMABLOK^{3}®

Characteristics
Antifungal
Mildew Resistant
Stain Resistant
No Heavy Metals
Formaldehyde Free

Performance
Superior Abrasion
CFFA 1-a, ASTM D-4157
100,000 cycles, Wyzenbeek #10 Cotton Duck

Cold Crack -20°F
CFFA 6-a

UV Stabilized Pigments
Xenotest: AATCC Blue Wool
1,000 hours

This fabric meets or exceeds these ACT performance guidelines.
*Certification Marks owned by ACT®

Flame Retardancy*
California T.B. 117- 2013
FMVSS 302
IMO FTP 2010
Code MSC.307(88), Part 8, 3.1 & 3.2
NFPA 260 - Class 1
UFAC - Class 1
Boston Fire Code
Federal Aviation Specification
Federal ST. 191A M 5903.1
Port Authorities of NY & NJ

*This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Specifics
Weight: 32 oz.
Width: 54 in.
Roll Size: 30 yd.

Applications
Corporate
Restaurant
Hospitality
Sunroom
Marine
Auto | RV
Residential Interiors

4/15/16