



DISTRIBUTORS OF LEATHER, VINYL, FABRIC & FOAM
4527 GLENWOOD ROAD • BROOKLYN, NY 11203
Phone: 718 941 3326 • Fax: 718 941 6115
Email: mark@dvcfabric.com

British Sterling Specifications:
Width
.....
. 54"
Roll Size
..... 30 yds.
Thickness
..... 1.0 mm
Nominal Weight
..... 30 oz. per Lin. yard
Contents
..... 100% Virgin Vinyl
Cold Crack
..... -10°F
UV Stabilized Pigments
300 hours mininum
Abrasion Resistance ... Wyzenbeek
(100K cycles #10 cotton duck)
Mildew Resistant (ASTM G-21)
..... Pass
Anti-Bacterial/Anti-Microbial
(AATCC 147) Pass
Suggested Applications:
Conference Seating, Executive
Seating, Office,
Residential, Hospitality, Lounge,
Healthcare,
Restaurant Seating
Meets Flammability
Requirements*:
Motor Vehicle Safety Standard 302
California Technical Bulletin 117-
2013, Section 1**
NFPA 260, Class 1
BIFMA, Class A
UFAC, Class 1
*This term and any corresponding
data refer to typical performance

in the specific test
indicated and should not be
construed to imply the behavior of
this or any other material
under actual fire conditions.
** This product, when tested with
suitable component materials,
may comply with
California Technical Bulletin 117-
2013, Section 1.
This product has been treated
with anti-bacterial
and anti-microbial agents that will
provide
resistance to the following:
(AATCC Test Method 147)
Bacillus Mycooides, Klebsiella
Pneumoniae, Proteus
Vulgaris, Staphylococcus Aureus,
Salmonella
Choleraesuis, Bacillus Cerus,
Enterococcus Faecalis,
Escherichia Coli