



DISTRIBUTORS OF LEATHER, VINYL, FABRIC & FOAM  
4527 GLENWOOD ROAD • BROOKLYN, NY 11203  
Phone: 718 941 3326 • Fax: 718 941 6115  
Email: mark@dvcfabric.com

## Surrey Specs

Suggested Applications: Durable Coated Fabric for Office Interior, Hospitality, Restaurant, Healthcare, Gaming, Residential, RV, Marine, Auto

Content: PVC

Backing: Q1 Polyester

Special Characteristics: Anti-Bacterial and Anti-Microbial (NYS63/ASTM G-21-90)

Performance:

Abrasion Resistance: Wyzenbeek (100,000 Cycles)

UV Stabilized Pigments: 500 Hours

Cold Crack: -10°F

Flammability Requirements: Motor Vehicle Safety Standard 302, California Technical Bulletin 117 Section E, New York & New Jersey Port Authority, Federal Aviation Specification 25.8553, Boston Fire Department Code, NFPA 260 Class1, BIFMA Class A, UFAC Class A, CID A-A-2950

Specifics:

Width: 54"

Roll Size: 30 Yards

Nominal Weight: 28 oz per Linear Yard

Thickness: 1 mm

Class Rating: ASTM D 3690 Class A