

## Verde

### Physical Specifications

**Weight (CFFA-700d)**

28 oz/lin yd [18.7 oz/yd<sup>2</sup>]

**Weight, Metric (CFFA-700d)**

849 g/lin m [619 g/m<sup>2</sup>]

**Width (CFFA-700a)**

54 in. [137 cm]

**Face Composition**

PVC

**Backing Description**

Polyester Terry Loop Knit

**Roll Size**

40 lin yd [37 lin m]

**Emboss Level**

Light

**Shipping Weight/ Roll**

68 lb [31 kg]

### Flame, Smoke & Toxicity

**Meets or exceeds the following:**

- BIFMA – Class A
- Cal Tech 117-2013 Sec 1
- NFPA 260 Class 1
- UFAC Fabric, Class 1

### Performance Features

**Protective Finish**

PreFixx

**Use**

Indoor

**Adhesion #/in., min (CFFA-3)**

4 Warp, 4 Fill

**Tensile Strength #, min (CFFA-17)**

85 Warp, 75 Fill

**Tack Strength #, min (CFFA-14)**

35 Warp, 30 Fill

**Trap Tear Strength #, min (CFFA-16c)**

20 Warp, 27 Fill

**Wyzenbeek Abrasion (CFFA-1a)**

1,300,000 Cotton Duck (double rubs)

**Blocking (CFFA-4 No. 1)**

Pass

**W-Flex – 25,000 cycles (CFFA-10)**

Pass

**Crocking Resistance – 20 cycles no stain (CFFA-7)**

Pass

**Cold Crack (CFFA-6a)**

-20 °F [-29 °C]

**Compatible with Disinfectants**

Yes. See Chem Resistance Tech Bulletin for more information.

**Bleach-Safe**

Yes, 10% Bleach Solution