



DISTRIBUTORS OF LEATHER, VINYL, FABRIC & FOAM  
4527 GLENWOOD ROAD • BROOKLYN, NY 11203  
Phone: 718 941 3326 • Fax: 718 941 6115  
Email: mark@dvcfabric.com

Zealand Specifications:

Width .....  
.....  
. 54"  
Roll Size .....  
..... 30 yds.  
Thickness .....  
..... 1.0 mm  
Nominal Weight .....  
..... 30 oz. per Lin. yard  
Contents .....  
..... 100% Virgin Vinyl  
Cold Crack .....  
..... -10°F  
UV Stabilized Pigments .....  
300 hours mininum  
Abrasion Resistance ... Wyzenbeek  
(100K cycles #10 cotton duck)  
Mildew Resistant (ASTM G-21) .....  
..... Pass  
Anti-Bacterial/Anti-Microbial  
(AATCC 147) ..... Pass  
Suggested Applications:  
Conference Seating, Executive  
Seating, Office,  
Residential, Hospitality, Lounge,  
Healthcare,  
Restaurant Seating  
Meets Flammability  
Requirements\*:  
Motor Vehicle Safety Standard 302  
California Technical Bulletin 117-  
2013, Section 1\*\*  
NFPA 260, Class 1  
BIFMA, Class A  
UFAC, Class 1  
\*This term and any corresponding  
data refer to typical performance

in the specific test  
indicated and should not be  
construed to imply the behavior of  
this or any other material  
under actual fire conditions.  
\*\* This product, when tested with  
suitable component materials,  
may comply with  
California Technical Bulletin 117-  
2013, Section 1.  
This product has been treated  
with anti-bacterial  
and anti-microbial agents that will  
provide  
resistance to the following:  
(AATCC Test Method 147)  
Bacillus Mycoides, Klebsiella  
Pneumoniae, Proteus  
Vulgaris, Staphylococcus Aureus,  
Salmonella  
Choleraesuis, Bacillus Cerus,  
Enterococcus Faecalis,  
Escherichia Coli