

This spec sheet has been updated to reflect the removal of flame retardant and anti-bacterial additives.

## Seaquest

### GENERAL SPECIFICATIONS

<b>SURFACE COMPOSITION</b>	100% PVC
<b>SUBSTRATE COMPOSITION</b>	100% Polyester
<b>WEIGHT</b>	32 oz per linear yard
<b>WIDTH</b>	54"
<b>THICKNESS</b>	1.02 mm

### ADDED PERFORMANCE SPECIFICATIONS

<b>STAIN RESISTANCE</b>	Yes	
<b>COLORFASTNESS TO LIGHT</b>	1,000 Hours	AATCC 16.3-2014, Option 3
<b>COLORFASTNESS TO UV</b>	1,000 Hours	ASTM G154-12a
<b>MILDEW RESISTANCE</b>	Pass	ASTM G21-00
<b>BLEACH RESISTANCE</b>	Yes, 10% Dilution	
<b>COLD CRACK</b>	-20° F	CFFA-6a-2007
<b>PINK STAIN RESISTANCE</b>	Pass	ASTM E1428
<b>SULFIDE STAIN RESISTANCE</b>	Yes	

### PHYSICAL PERFORMANCE SPECIFICATIONS

<b>ABRASION RESISTANCE</b>	175,000 Double Rubs*	ASTM D4157-13
<b>BREAKING STRENGTH</b>	89.2 Warp, 102.7 Fill	ASTM D751-06
<b>FLEX RESISTANCE</b>	25,000+	ASTM D2097-03

\*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

### FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13	Pass
UFAC CLASS I	Pass
NFPA 260	Pass
FMVSS 302	Pass

### REDUCED ENVIRONMENTAL IMPACT

- THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65
- NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT
- NO ADDED ANTI-BACTERIAL CHEMICALS
- 7P PHTHALATE FREE
- LEAD / HEAVY METAL FREE
- BPA FREE / TRIS FREE / FORMALDEHYDE FREE
- DOES NOT CONTAIN CONFLICT MINERALS



\*ACT® Registered Certification Marks