

Hawthorne

This is an up-to-date spec sheet. This pattern never contained flame retardant, anti-bacterial, or anti-microbial additives.

GENERAL SPECIFICATIONS

SURFACE COMPOSITION 95% Polyurethane (Polycarbonate) / 5% Silicone

SUBSTRATE COMPOSITION100% PolyesterWEIGHT19 oz per linear yard

 WIDTH
 54"

 THICKNESS
 1.00 mm

ADDED PERFORMANCE SPECIFICATIONS

HYDROLYSIS RESISTANCE 15 weeks ISO 1419:1995 (Jungle Test)

STAIN RESISTANCE Yes

COLORFASTNESS TO LIGHT 200 Hours AATCC 16.3-2014, Option 3

BLEACH RESISTANCE Yes, 10% Dilution

MILDEW RESISTANCEPassASTM G21-13ANTI-BACTERIALPassAATC 147-2011COLD CRACK-20° FCFFA-6a-2007DENIM DYE TRANSFER RESISTANCEYesFord BN 112-09

SULFIDE STAIN RESISTANCE Yes

PHYSICAL PERFORMANCE SPECIFICATIONS

ABRASION RESISTANCE 250,000+ Double Rubs* ASTM D4157-13 **BREAKING STRENGTH** 118 Warp, 96 Fill ASTM D751-06 **COATING ADHESION** Full Bond Warp, Full Bond Fill ASTM D751-06 **CROCKING RESISTANCE** 5 Dry, 5 Wet **AATCC 8-2016 FLEX RESISTANCE** 25,000+ ASTM D2097-03 **TEAR STRENGTH: TONGUE TEAR** 10.4 Warp. 12.1 Fill ASTM D751-06 **SEAM STRENGTH: TACK TEAR** ASTM D751-06 69.52 Warp, 62.44 Fill

*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13 Pass
UFAC CLASS I Pass
NFPA 260 Pass

REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65
NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT
NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS
LEAD / HEAVY METAL FREE
BPA FREE / TRIS FREE / FORMALDEHYDE FREE
DOES NOT CONTAIN CONFLICT MINERALS



Disclaimer: This product meets the Healthy Interior goals of the Safer Chemical Challenge according to the manufacturer Practice Greenhealth does not verify this information

