

# Nassimi

PRODUCT SPECIFICATION SHEET



## RESILIENCE

The faux leather that builds luxury into performance

This is an up-to-date spec sheet. This pattern never contained flame retardant, anti-bacterial, or anti-microbial additives.

## Notion

### GENERAL SPECIFICATIONS

<b>SURFACE COMPOSITION</b>	100% PVC (Phthalate Free)
<b>SUBSTRATE COMPOSITION</b>	100% Polyester
<b>WEIGHT</b>	31 oz per linear yard
<b>WIDTH</b>	54"
<b>THICKNESS</b>	1.20 mm

### ADDED PERFORMANCE SPECIFICATIONS

<b>STAIN RESISTANCE</b>	Yes	
<b>COLORFASTNESS TO LIGHT</b>	300 Hours	AATCC 16.3-2014, Option 3
<b>BLEACH RESISTANCE</b>	Yes, 10% Dilution	
<b>COLD CRACK</b>	-20° F	CFFA-6a-2007
<b>DENIM DYE TRANSFER RESISTANCE</b>	Yes	
<b>SULFIDE STAIN RESISTANCE</b>	Yes	

### PHYSICAL PERFORMANCE SPECIFICATIONS

<b>ABRASION RESISTANCE</b>	250,000+ Double Rubs*	ASTM D4157-13
<b>BREAKING STRENGTH</b>	95 Warp, 73 Fill	ASTM D751-06
<b>COATING ADHESION</b>	8.0 Warp, 8.1 Fill	ASTM D751-06
<b>CROCKING RESISTANCE</b>	5 Dry, 5 Wet	AATCC 8-2016
<b>FLEX RESISTANCE</b>	25,000+	ASTM D2097-03
<b>TEAR STRENGTH: TONGUE TEAR</b>	7.2 Warp, 11.0 Fill	ASTM D751-06
<b>SEAM STRENGTH: TACK TEAR</b>	48.8 Warp, 40.0 Fill	ASTM D751-06

*\*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.*

### FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13	Pass
UFAC CLASS I	Pass
NFPA 260	Pass
FMVSS 302	Pass

### REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65  
NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT  
NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS  
PHTHALATE FREE  
LEAD / HEAVY METAL FREE  
BPA FREE / TRIS FREE / FORMALDEHYDE FREE  
DOES NOT CONTAIN CONFLICT MINERALS



\*ACT® Registered Certification Marks

