

Huron

GENERAL SPECIFICATIONS

WEIGHT (LINEAR YARD)

WIDTH

COMPOSITION

☐ PIFCF DYFD

DOBBY

☐ YARN DYFD

☐ JACQUARD

YARN PFR INCH YARN SIZE BACKING

MINIMUM YARDAGE CUSTOM COLOR

CLEANING CODE

17 oz per linear yard

54"

91% Polyester / 7% Polyurethane / 2% Silicone

■ FIBER DYFD

□ PILE

29.7 EPI, 26.6 PPI 1250D Warp, 1250D Fill

Polyurethane 500 Yards

SW, Spot clean with upholstery shampoo, foam from a mild detergent, or a mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion cover should not be removed and dry cleaned.

BC, Lightly spray with a 10% dilution of Household Bleach and water. After the appropriate contact time, blot surface dry and wipe or rinse with fresh water and blot dry.

PHYSICAL PERFORMANCE SPECIFICATIONS

ABRASION RESISTANCE 100,000+ Double Rubs* HYDROSTATIC PRESSURE (SUTER) 270+cm (maximum) BREAKING STRENGTH 225 Warp, 195 Fill **BRUSH PILL** Class 4 CROCKING RESISTANCE 4.5 Dry, 5 Wet COLORFASTNESS TO LIGHT Class 5, 40 hours SEAM SLIPPAGE 88.5 Warp, 89.5 Fill WATER REPELLENCY SPRAY TEST TEAR STRENGTH: TONGUE TEAR 46 Warp, 44.4 Fill Yes, 10% Dilution **BLEACH RESISTANCE**

ASTM D4157-13 AATCC 127-13, Option 1 ASTM D5034-09 **ASTM D3511 AATCC 8-2016** AATCC 16.3-2014 ASTM D4034-92 AATCC 22-2014 ASTM D2261-13

*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13 Pass UFAC CLASS I Pass **NFPA 260** Pass

REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65 NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS LEAD / HEAVY METAL FREE BPA FREE / TRIS FREE / FORMALDEHYDE FREE

DOES NOT CONTAIN CONFLICT MINERALS









Disclaimer: This product meets the Healthy Interior goals of the Safer Chemical Challenge according to the manufacturer Practice Greenhealth does not verify this information.





