

## Chrystie

### GENERAL SPECIFICATIONS

WEIGHT (LINEAR YARD)

18.5 oz per linear yard

WIDTH

54"

COMPOSITION

100% Polyester

☒ PIECE DYED

☐ YARN DYED

☐ FIBER DYED

☒ DOBBY

☐ JACQUARD

☐ PILE

YARN PER INCH

81.3 EPI, 40.6 PPI

YARN SIZE

T300D+T10S Warp, T300D+T5.6N Fill

BACKING

SBR

STAIN RESISTANCE

C6

CLEANING CODE

SW, Spot clean with upholstery shampoo, foam from a mild detergent, or a mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion cover should not be removed and dry cleaned.

### PHYSICAL PERFORMANCE SPECIFICATIONS

ABRASION RESISTANCE

100,000+ Double Rubs\*

ASTM D4157-13

BREAKING STRENGTH

340 Warp, 167 Fill

ASTM D5034-09

BRUSH PILL

Class 4.5

ASTM D3511

CROCKING RESISTANCE

5 Dry, 5 Wet

AATCC 8-2013

COLORFASTNESS TO LIGHT

Class 4

AATCC 16.3-2012, Option 3

SEAM SLIPPAGE

82.9 Warp, 71.8 Fill

ASTM D4034-92

TEAR STRENGTH: TONGUE TEAR

70.1 Warp, 36.7 Fill

ASTM D2261-13

*\*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.*

### FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13

Pass

UFAC CLASS I

Pass

NFPA 260

Pass

### REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65

NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT

NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS

LEAD / HEAVY METAL FREE

BPA FREE / TRIS FREE / FORMALDEHYDE FREE

DOES NOT CONTAIN CONFLICT MINERALS



\*ACT® Registered Certification Marks