
ELYSI9009 - 9009 Black



Product Description

"Elysium 9009 Black is the next generation of PVC performance in a brilliant black color with a connecting lines pattern. It features a buttery soft hand, Endurepel Armour performance finish, and excellent durability."

Cleaner Disclaimer

Dilution ratios must be followed. Materials must be wiped with clean water after use to remove any cleaning residue and wiped dry with a clean cloth.

Cleaners Approved

["Cleanable with Bleach", "Cleanable with Diluted 1 Accel Five TB.", "Cleanable with Diluted 1 Virox 5.", "Cleanable with Diluted 1 Oxiver Plus", "Cleanable with Diluted 1 Oxiver TB Plus", "Cleanable with Diluted 1 Accel test footer

SPECIFICATIONS	
Abrasion	1,500,000 Double Rubs (Wyzenbeek)
After Treatment Finish	Stock Finished with Endurepel Armour
Brand	GUARDIAN
Construction	Polyvinyl Chloride Coated Faux Leather Fabric
Content Backing	["100% Polyester"]
Content Face	["100% Vinyl"]
Crocking	AATCC 8: Dry crocking = Class 5
Fire Retardancy	CALTB117-2013, IMO FTP 2010 Code MSC.307(88), Part 8, 3.1 & 3.2, MVSS302, NFPA 260 Class 1, UFAC Class 1
Number of Colors	Available in 7 colors
Railroaded	Non Railroaded
Roll Size	30 yds (27 m)
Seam Slippage	ASTM D751 Fill 64 X Warp 67 lb
Tensile Strength	Passes ASTM D751 - Weft 94 x Warp 101

ELYSI9009 - 9009 Black

Concentrate", "Cleanable with		
Diluted 1 Isopropyl		
Alcohol", "Cleanable with Clorox		
Disinfecting Wipes", "Cleanable		
with Diluted 1 Oasis 146"]		

Cleaning Code

["W - Clean fabrics with waterbased cleaning agents or water based foam"]

Industry

["Contract", "Fitness", "Healthcare' OEM", "Office Seating", "Residential", "RV", "Tran

Uses

Automotive Seating, Bags, Decorative Accessories, Healthcare Seating, Hospitality Seating, Marine Seating, Office Seating, Residential Seating, RV Seating

SPECIFICATIONS	
["700 gsm","30.96 oz/yd","20.64 oz/sq yd"]	
54 in. (137 cm)	
The Guardian Collection has a limited 3-year fabric warranty against becoming unserviceable due to loss of colour, loss of strength, abrasion and pilling from normal usage and exposure conditions	
This product is Proposition 65 compliant	