

## SPECIFICATIONS

<b>Abrasion</b>	1,500,000 Double Rubs (Wyzenbeek)
<b>After Treatment Finish</b>	Stock Finished with Endurepel Armour
<b>Brand</b>	GUARDIAN
<b>Construction</b>	Polyvinyl Chloride Coated Faux Leather Fabric
<b>Content Face</b>	100% Vinyl
<b>Crocking</b>	AATCC 8: Dry crocking = Class 5
<b>Fire Retardancy</b>	CALTB117-2013, IMO FTP 2010 Code MSC.307(88), Part 8, 3.1 & 3.2, MVSS302, NFPA 260 Class 1, UFAC Class 1
<b>Number of Colors</b>	Available in 8 colors
<b>Railroaded</b>	Non Railroaded
<b>Roll Size</b>	30 yds (27 m)
<b>Seam Slippage</b>	ASTM D751 Fill 64 X Warp 67 lb
<b>Tensile Strength</b>	Passes ASTM D751 - Weft 94 x Warp 101
<b>Weight</b>	700 gsm



### Product Description

"Gilded 405 Sandalwood is the next generation of PVC performance in a rich, dark orange color with a high gloss leather grain. It features a buttery soft hand, Endurepel Armour performance finish, and excellent durability."

### Cleaner Disclaimer

Dilution ratios must be followed. Materials must be wiped with clean water after use to remove any cleaning residue and wiped dry with a clean cloth.

### Cleaners Approved

Cleanable with Bleach Cleanable with Diluted 1 Accel Five TB. Cleanable with Diluted 1 Virox 5. Cleanable with Diluted 1 Oxiver Plus Cleanable with Diluted 1 Oxiver TB Plus Cleanable with Diluted 1 Accel Concentrate test footer

## SPECIFICATIONS

Cleanable with Diluted 1  
Isopropyl Alcohol Cleanable with  
Clorox Disinfecting Wipes  
Cleanable with Diluted 1 Oasis  
146

### Cleaning Code

W - Clean fabrics with water-  
based cleaning agents or water  
based foam

### Industry

Contract Fitness Healthcare  
Hospitality Marine OEM Office  
Seating Residential RV  
Transportation

### Uses

Automotive Seating, Bags,  
Decorative Accessories,  
Healthcare Seating, Hospitality  
Seating, Marine Seating, Office  
Seating, Residential Seating, RV  
Seating

<b>Width</b>	54 in. (137 cm)
--------------	-----------------

<b>Warranty</b>	The Guardian Collection has a limited 3-year fabric warranty against becoming unserviceable due to loss of colour, loss of strength, abrasion and pilling from normal usage and exposure conditions
-----------------	---

<b>Proposition 65</b>	This product is Proposition 65 compliant
-----------------------	--