

Sonic

GENERAL SPECIFICATIONS

| | |
|------------------------------|------------------------------|
| SURFACE COMPOSITION | 100% PVC (7P Phthalate Free) |
| SUBSTRATE COMPOSITION | 100% Polyester |
| WEIGHT | 32 oz per linear yard |
| WIDTH | 54" |
| THICKNESS | 1.02 mm |

ADDED PERFORMANCE SPECIFICATIONS

| | | |
|---------------------------------|-------------------|---------------------------|
| STAIN RESISTANCE | Yes | |
| COLORFASTNESS TO LIGHT | 1,000 Hours | AATCC 16.3-2014, Option 3 |
| COLORFASTNESS TO UV | 1,000 Hours | ASTM G154-12a |
| MILDEW RESISTANCE | Pass | ASTM G21-00 |
| BLEACH RESISTANCE | Yes, 10% Dilution | |
| COLD CRACK | -20° F | CFFA-6a-2007 |
| PINK STAIN RESISTANCE | Pass | ASTM E1428 |
| SULFIDE STAIN RESISTANCE | Yes | |

PHYSICAL PERFORMANCE SPECIFICATIONS

| | | |
|-----------------------------------|----------------------|---------------|
| ABRASION RESISTANCE | 100,000 Double Rubs* | ASTM D4157-13 |
| COATING ADHESION | 7.6 Warp, 4.6 Fill | ASTM D751-06 |
| CROCKING RESISTANCE | 5 Dry, 5 Wet | AATCC 8-2007 |
| BREAKING STRENGTH | 110 Warp, 79 Fill | ASTM D751-06 |
| FLEX RESISTANCE | 25,000+ | ASTM D2097-03 |
| TEAR STRENGTH: TONGUE TEAR | 11.9 Warp, 12.8 Fill | ASTM D751-06 |
| SEAM STRENGTH: TACK TEAR | 69.6 Warp, 43.2 Fill | ASTM D751-06 |

*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

FLAME RETARDANCY SPECIFICATIONS

| | |
|--------------------------------------|------|
| CALIFORNIA TECHNICAL BULLETIN 117:13 | Pass |
| UFAC CLASS I | Pass |
| NFPA 260 | Pass |
| FMVSS 302 | Pass |

REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65
 NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT
 NO ADDED ANTI-BACTERIAL CHEMICALS
 7P PHTHALATE FREE
 LEAD / HEAVY METAL FREE
 BPA FREE / TRIS FREE / FORMALDEHYDE FREE
 DOES NOT CONTAIN CONFLICT MINERALS



*ACT® Registered Certification Marks