

PRODUCT SPECIFICATION SHEET



This is an up-to-date spec sheet. This pattern never contained flame retardant, anti-bacterial, or anti-microbial additives.

Bradbury

GENERAL SPECIFICATIONS

| | |
|------------------------------|-------------------------|
| SURFACE COMPOSITION | 100% Polyurethane |
| SUBSTRATE COMPOSITION | 100% Polyester |
| WEIGHT | 25.4 oz per linear yard |
| WIDTH | 54" |
| THICKNESS | 1.40mm |

ADDED PERFORMANCE SPECIFICATIONS

| | | |
|--------------------------------------|-------------------|-----------------------------|
| HYDROLYSIS RESISTANCE | 10 weeks | ISO 1419:1995 (Jungle Test) |
| STAIN RESISTANCE | Yes | |
| COLORFASTNESS TO LIGHT | 200 Hours | AATCC 16.3-2014, Option 3 |
| BLEACH RESISTANCE | Yes, 10% Dilution | |
| COLD CRACK | -20° F | CFFA-6a-2007 |
| DENIM DYE TRANSFER RESISTANCE | Yes | Ford BN 112-09 |
| SULFIDE STAIN RESISTANCE | Yes | |

PHYSICAL PERFORMANCE SPECIFICATIONS

| | | |
|-----------------------------------|---|---------------|
| ABRASION RESISTANCE | 250,000+ Double Rubs* | ASTM D4157-13 |
| BLOCKING | Rating 1 | CFFA-4 |
| BREAKING STRENGTH | 127 Warp, 233 Fill | ASTM D751-06 |
| COATING ADHESION | 3.73 Warp, 3.73 Fill | ASTM D751-06 |
| CROCKING RESISTANCE | 5 Dry, 5 Wet | AATCC 8-2016 |
| FLEX RESISTANCE | 25,000+ | ASTM D2097-03 |
| TEAR STRENGTH: TONGUE TEAR | 9.3 Warp, 12.2 Fill | ASTM D751-06 |
| SEAM STRENGTH: TACK TEAR | 83.9 Warp, 82.5 Fill | ASTM D751-06 |
| STRETCH AND SET | Warp 8.33% Stretch, 0.69% Set Fill 29.41% Stretch, 1.73% Set | SAE J855-2009 |

*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

FLAME RETARDANCY SPECIFICATIONS

| | |
|--------------------------------------|------|
| CALIFORNIA TECHNICAL BULLETIN 117:13 | Pass |
| UFAC CLASS I | Pass |
| NFPA 260 | Pass |

REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65
NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT
NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS
LEAD / HEAVY METAL FREE
PFC/PFOA FREE
BPA FREE / TRIS FREE / FORMALDEHYDE FREE
DOES NOT CONTAIN CONFLICT MINERALS



*ACT® Registered Certification Marks



Disclaimer: This product meets the Healthy Interior goals of the Safer Chemical Challenge according to the manufacturer Practice Greenhealth does not verify this information.