



PRODUCT SPECIFICATION SHEET

# Carlisle

## GENERAL SPECIFICATIONS

WEIGHT (LINEAR YARD)	17.8 oz per linear yard
WIDTH	54"
COMPOSITION	85% Polyester / 15% Cotton
<input type="checkbox"/> PIECE DYED	<input checked="" type="checkbox"/> YARN DYED
<input type="checkbox"/> DOBBY	<input checked="" type="checkbox"/> JACQUARD
	<input type="checkbox"/> FIBER DYED
	<input type="checkbox"/> PILE
YARN PER INCH	25.9 EPI, 6.7 PPI
YARN SIZE	150 DN Warp, 8/1 NE COTTON + 300 DEN PES + 4100DEN PES Fill
BACKING	ACRYLIC
STAIN RESISTANCE	C0
CLEANING CODE	SW, Spot clean with upholstery shampoo, foam from a mild detergent, or a mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion cover should not be removed and dry cleaned.

## PHYSICAL PERFORMANCE SPECIFICATIONS

ABRASION RESISTANCE	100,000 Double Rubs*	ASTM D4157-13
BREAKING STRENGTH	244 Warp, 222 Fill	ASTM D5034-09
BRUSH PILL	Class 4.2	ASTM D3511
CROCKING RESISTANCE	5 Dry, 5.0 Wet	AATCC 8-2013
COLORFASTNESS TO LIGHT	Class 5	AATCC 16.3-2014, Option 3
SEAM SLIPPAGE	108 Warp, 41.5 Fill	ASTM D4034-92
TEAR STRENGTH: TONGUE TEAR	26.3 Warp, 34.3 Fill	ASTM D2261-13

\*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

## FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13	Pass
UFAC CLASS I	Pass
NFPA 260	Pass

## REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65  
NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT  
NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS  
LEAD / HEAVY METAL FREE  
BPA FREE / TRIS FREE / FORMALDEHYDE FREE  
DOES NOT CONTAIN CONFLICT MINERALS



\*ACT® Registered Certification Marks