

# DISTRIBUTORS OF LEATHER, VINYL, FABRIC & FOAM 4527 GLENWOOD ROAD • BROOKLYN, NY 11203

Phone: 718 941 3326 • Fax: 718 941 6115

Email: mark@dvcfabric.com

SiO<sup>™</sup>

The medical performance grade silicone™

## This is an up-to-date spec sheet. This pattern never contained flame retardant, antibacterial, or anti-microvial additives.

### PRODUCT SPECIFICATION SHEET

# **Envision**

SURFACE COMPOSITION 100% SiO™ Silicone SUBSTRATE COMPOSITION 100% Polyester **WEIGHT** 28 oz per linear yard

**WIDTH** 54" **THICKNESS** 1.10 mm

## ADDED PERFORMANCE SPECIFICATIONS

**STAIN RESISTANCE** Yes

**UV RESISTANCE** 1300 Hours ASTM G154-06

**COLORFASTNESS TO LIGHT** 500 Hours AATCC 16.3-2014, Option 3

**BLEACH RESISTANCE** Yes. 10% Dilution

**MILDEW RESISTANCE** Pass ASTM G21-13 **ANTI-BACTERIAL** Pass AATCC 147-11 **COLD CRACK** -20° F CFFA-6a-2010 **DENIM DYE TRANSFER RESISTANCE** Yes Ford BN 112-09

**SULFIDE STAIN RESISTANCE** Yes

**PINK STAIN RESISTANCE** Yes **ASTM E1428 ANTI-STATIC** Pass AATCC-76 CYTOTOXICITY Degree 0 ISO 10993-5 **SKIN IRRITATION** No reaction ISO 10993-10 **SALT SPRAY RESISTANCE** 1.000+ Hours ASTM B117

**INK RESISTANCE** Yes

ISOPROPYL ALCOHOL RESISTANCE Yes. 70% Dilution

## PHYSICAL PERFORMANCE SPECIFICATIONS

**ABRASION RESISTANCE** 225,000 Double Rubs\* ASTM D4157-13 **BREAKING STRENGTH** 250 Warp, 279 Fill ASTM D751-00 **COATING ADHESION** Full Bond Warp, Full Bond Fill ASTM D751-06 **CROCKING RESISTANCE** 5 Dry, 5 Wet **AATCC 8-2016 FLEX RESISTANCE** 25,000+ ASTM D2097-03 **TEAR STRENGTH: TONGUE TEAR** ASTM D751-06 10.7 Warp, 11.8 Fill **SEAM STRENGTH: TACK TEAR** 88.9 Warp, 97.84 Fill ASTM D751-06

Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

## FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13 **Pass** UFAC CLASS I Pass **NFPA 260** Pass IMO 2010 FTP CODE, PT. 8 Pass ASTM E84 (ADHERED & UNADHERED) Pass BS 5852: 2006 Crib 5 Pass FMVSS 302 Pass

# REDUCED ENVIRONMENTAL IMPACT

BPA FREE / TRIS FREE / FORMALDEHYDE FREE

DOES NOT CONTAIN CONFLICT MINERALS

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65 NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT NO ADDED ANTI-BACTERIAL CHEMICALS PHTHALATE FREE LEAD / HEAVY METAL FREE







\*ACT® Registered Certification Marks

