
Swank



## Specifications:

100% Polyester content:

Synthetic latex blend backing:

i-clean, a high-performance stain repellant based finish:

on Nano technology

Repeat: N/A

weight: 11.36 oz. / lin. yd.

width: 54 inches

## Flammability Passes:

California Tech. Bulletin #117-2013 **UFAC Class 1** NFPA 260 Class 1

## Performance:

Heavy Duty - 100,000 cycles abrasion:

(Wyzenbeek - Cotton duck Abradant) (ASTM D4157)

Class 4/40 hrs. min. (AATCC16A) light fastness: Class 3 (ASTM D3597, AATCC 8) Wet color fastness:

Class 4 (ASTM D3597, AATCC 8) Dry

Class 3 (ASTM D3511) Brush Pill physical properties:

> 93 lbs. warp, 117 lbs. weft (ASTM D5034) Breaking Strength 44 lbs. warp, 41 lbs. weft (ASTM D4034) Seam Slippage

China made in:

## Care & Cleanability:

Cleaning code W - Spot clean only with water-based upholstery shampoo or foam upholstery cleaner. Pretest a small, inconspicuous area before proceeding. Do not over wet. Do not use solvents to spot clean. Cushion covers should not be removed and laundered. When cleaning a spill, blot immediately to remove the spilled material. Evenly clean the entire panel in a seam to seam fashion. Do not clean just the spots or stains. When an overall soiled condition has been reached and professional care is required, contact an IICRC certified firm (www.iicrc.org).



Email: mark@dvcfabric.com