

NASSIMI

PRODUCT SPECIFICATION SHEET



Victoria

GENERAL SPECIFICATIONS

WEIGHT	18 oz per linear yard
WIDTH	54"
COMPOSITION	94% Polyester /2% Silicone/4% TPU
<input type="checkbox"/> DIGITAL PRINT	<input type="checkbox"/> FIBER DYED
<input checked="" type="checkbox"/> DOBBY	<input type="checkbox"/> PILE
<input checked="" type="checkbox"/> YARN DYED	
<input type="checkbox"/> JACQUARD	
YARN PER INCH	84 EPI, 41 PPI
YARN SIZE	T3.5N+T5.5N+T300D Warp, T3.5N+T5.5N+T10N Fill
BACKING	TPU
CLEANING CODE	SW, Spot clean with upholstery shampoo, foam from a mild detergent, or a mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion cover should not be removed and dry cleaned.

PHYSICAL PERFORMANCE SPECIFICATIONS

ABRASION RESISTANCE	100,000+ Double Rubs*	ASTM D4157-13
BRUSH PILL	Class 5	ASTM D3511
HYDROSTATIC PRESSURE (SUTER)	270+cm (maximum)	AATCC 127-2013, Option 1
CROCKING RESISTANCE	4.5 Dry, 5 Wet	AATCC 8-2016
COLORFASTNESS TO LIGHT	Class 5	AATCC 16.3-2014, Option 3
SEAM SLIPPAGE	116 Warp, 75 Fill	ASTM D4034-92
WATER REPELLENCY SPRAY TEST	100	AATCC 22-2014
TEAR STRENGTH: TONGUE TEAR	32 Warp, 23.3 Fill	ASTM D2261-13
BREAKING STRENGTH	272 Warp, 54.2 Fill	ASTM D5034-09

*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13	Pass
UFAC CLASS I	Pass
NFPA 260	Pass

REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65
NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT
NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS
LEAD / HEAVY METAL FREE
BPA FREE / TRIS FREE / FORMALDEHYDE FREE
DOES NOT CONTAIN CONFLICT MINERALS



Disclaimer: This product meets the Healthy Interior goals of the Safer Chemical Challenge according to the manufacturer Practice Greenhealth does not verify this information.



*ACT® Registered Certification Marks