

Yates

YATES44 - 44 Clay

SPECIFICATIONS



Product Description

Yates embodies a sophisticated textured textile, exuding a sense of refinement and elegance.

Cleaning Code

W - Clean fabrics with water-based cleaning agents or water based foam

Abrasion	350, 000 Double Rubs (Wyzenbeek)
After Treatment Finish	Stock unfinished. After treatment available with Endurepel Shield.
Construction	Woven Plain
Content Backing	100% Acrylic Kiss Coat
Content Face	100% Polyester
Crocking	CFFA 7 Federal Standard 191A M 5551: Dry crocking = Class 5
Fire Retardancy	CALTB117-2013, NFPA 260 Class 1
Number of Colors	Available in 30 colors
Railroaded	Railroaded
Roll Size	50 yds (46 m)
Seam Slippage	ASTM D4030 Fill 105 X Warp 96 lb
Tensile Strength	Passes ASTM D5034 - Weft 169 x Warp 323
Weight	420 gsm, 18.5 oz/yd, 12.3 oz/sq yd
Width	54 in. (137 cm)
Warranty	Full warranty of 2 years

SPECIFICATIONS

Proposition 65	This product is Proposition 65 compliant
Pilling	ASTM D3511 - Class 4
Social Responsibility	This product is sourced through a socially compliant vendor who has met our sustainability criteria.
Sustainable Manufacturing	ISO 14001 Certified, OEKOTEX Certified
Industry	Contract, Hospitality, Office Seating, Residential
Uses	Bedding, Decorative Accessories, Office Seating, Pillows, Residential Seating