

## Carmen

## General

Contents (Face)		
Contents (Backing)		
Fabric Type		
Backing Type		
Overall Weight		
Usable Width		
Performance Finish		
Prepared for Print		
Dye Method		
Custom Color		
Production Lead Time		
Origin		
HTS Code		
Environmental		

100% Polyester			
100% Polyester			
Warp Knit			
Brushed Knit			
16.4 oz/linear yard, 370 g/sm			
54"			
C-Zero Stain Treatment			
Yes			
Piece Dyed			
500 Meters			
15-20 days			
Turkey			
6005.37.00			
STANDARD 100 by OEKO-TEX ® , Class I			

Specifications	Test Method	Result
Light Fastness	AATCC 16.3:2012 Option 3	Grade 4.5 @40 hours
Crocking: Dry	AATCC 8:2016	Grade 4.5
Crocking: Wet	AATCC 8:2016	Grade 4.5
Seam Slippage: Warp	ASTM D4034	120.1 lbs
Seam Slippage: Weft	ASTM D4034	145.2 lbs
Seam Slippage: Opening @ 6mm: Warp	ASTM D4034	90.8 lbs
Seam Slippage: Opening @ 6mm: Weft	ASTM D4034	138.1 lbs
Tear Strength: Warp	ASTM D2261:2013	11.9 lbs
Tear Strength: Weft	ASTM D2261:2013	13.2 lbs
Tensile Strength: Warp	ASTM D5034:2009	200.2 lbs
Tensile Strength: Weft	ASTM D5034:2009	186.9 lbs
Surface Abrasion- Wyzenbeek	ASTM D4157	>102,000 (cotton duck)
Brush Pilling	ASTM D3511	Class 5
Flame Retardancy	CAL TB 117-2013	Pass (without treatment)
	NFPA 260 / UFAC	Class 1 (without treatment)
	NFPA 701	Treatment required
	IMO 2010 Part 8	Treatment required

\*Please note this document is our own consolidation of all test results for the article listed above and not the original test report. Original test reports from accredited US and international laboratories can be provided upon request.