

White



Ivory



Camel




Lipstick




Ocean



Pear



Pumice



Stone




Brick




Port




Sapphire




Pine



Jet




Charcoal



Bark



Raisin



Grotto

Construction

Surface Composition
Backing Composition
Finished Width
Repeat
Railroaded
Put-up
Cleaning Code
Stain Resistant

Values

100% Polyurethane
100% Polyester
54" min.
None
No
30 yards
W/S
Yes

Test Method

ASTM D 751-06
ASTM D 751-06

Performance

Grab Tensile
Trap Tear
Seam Strength
Adhesion
Stretch @ 15# MD (warp) × CD (fill)
Flex Resistance
Blocking
Crock Resistance
Wyzenbeek Abrasion
Hydrolysis Resistance
Colorfastness to Light
Blue Dye Transfer Resistance
Anti-Bacterial
Mildew Resistance
Cold Crack (#5 roller)

Values

80 lbs./in. × 80 lbs./in.
15 lbs./in. × 15 lbs./in.
40 lbs./in. × 40 lbs./in.
4 lbs./in. × 4 lbs./in.
2% × 7%
25,000 cycles
No. 1 - Pass
Dry-4; Wet-4
300,000 cycles, #10 Cotton Duck
10 weeks
200 hours
Dry-4-5; Wet-4-5
Pass
Pass
-20°F

Test Method

ASTM D 751-06
ASTM D 751-06
ASTM D 751-06
ASTM D 751-06
ASTM D 751-06
ASTM D 2097-91
Fed. Std. 191 A , 5872
AATCC 8-2007
ASTM D 4157-07
ASTM D 3690-02; ISO 1419: 1995
ASTM D 4329-05
LP-463KC-04-03
AATCC 147-2004
ASTM G-21
CFFA-6A

Flammability

California Technical Bulletin 117-2013, Sec. 1	Pass
IMO A.652(16)8.2	Pass
NFPA 260	Pass
U.F.A.C. Class I	Pass

Environmental

1. No anti-microbial additives
2. Does not contain PFAS, PFOA
3. Prop 65 compliant
4. No chemical flame retardants, CA AB2998 compliant
5. REACH, RoHS, and LEED compliant

Suitable Applications Contract, Healthcare, Hospitality, Residential

Cleaning and Disinfecting

Remove ordinary dirt and smudges with mild soap and water. A 10:1 ratio of water to bleach solution may be used as a disinfectant. Rinse the surface with clean water after disinfecting. Dry with a soft, lint-free cloth or towel. We recommend that you use Clorox Healthcare and Clorox Pro products to disinfect products in commercial settings.