

ASPIRATIONS

PRODURATECT™

ASPIRATIONS with PRODURATECT™ is manufactured to meet the following typical properties:

Specifications:

Width 54"
 Roll Size 30 yds.
 Thickness 1.02 mm
 Nominal Weight 27 oz. per linear yard
 Contents PVC
 Backing Polyester
 Cold Crack -10°F
 UV Stabilized Pigments 300 hours minimum
 Abrasion Resistance† Wyzenbeek:
 (100K cycles #10 cotton duck)

Meets Flammability Requirements*:

California Technical Bulletin 117-2013, Section 1**
 NFPA 260, Class 1
 BIFMA, Class A
 UFAC, Class 1

*This term and any corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

** This product, when tested with suitable component materials, may comply with California Technical Bulletin 117-2013, Section 1

Suggested Applications:

Healthcare, Hospitality, Marine Interior, Office,
 Residential, Restaurant, RV

Other Attributes:

Flame Retardant Additive Free
 Phthalate Free
 Anti-Mildew Additive Free
 Anti-Microbial/Anti-Bacterial Additive Free



This fabric meets or exceeds these ACT performance guidelines. Certification Marks owned by ACT.

† Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

Cleaning Instructions:

This product should be cleaned with mild soap and water. Do not use alcohol based cleaners.

ENDURATEX™ and PRODURATECT™ are trademarks of CGPC America Corp. and may not be used without written permission of CGPC America Corp.

