

CRAFTED GRIDS

Enduraprint

CRAFTED GRIDS with PRODURATECT™ C is manufactured to meet the following typical properties:

Specifications:

Width 54"
Roll Size 30 yds.
Thickness 1.02 mm
Nominal Weight 29 oz. per Lin. yard
Contents 100% PVC
Backing Polyester/Rayon
Cold Crack -10°F
UV Stabilized Pigments 300 hours minimum
Abrasion Resistance ... Wyzenbeek (100K cycles #10 cotton duck)
Abrasion Resistance Print Taber (50K cycles ASTM 3884)
Class Ratings ASTM D 3690 - Class A
Mildew Resistance (ASTM G-21) Pass
Anti-Bacterial/Anti-Microbial (AATCC 147) Pass

Suggested Applications:

Contract, Healthcare, Hospitality, Office, Residential, Restaurant



* This fabric meets or exceeds these ACT performance guidelines. Certification Marks owned by ACT.

Meets Flammability Requirements*:

Motor Vehicle Safety Standard 302
California Technical Bulletin 117-2013, Section 1**
Boston Fire Department Code
FAR 25.853 (A) Appendix F Part 1 (a)(1)(ii)
NFPA 260, Class 1
BIFMA, Class A
UFAC, Class 1

*This term and any corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

** This product, when tested with suitable component materials, may comply with California Technical Bulletin 117-2013, Section 1

This product has been treated with anti-bacterial and anti-microbial agents that will provide resistance to the following:

(AATCC Test Method 147)

Bacillus Mycoides, Klebsiella Pneumoniae, Proteus Vulgaris, Staphylococcus Aureus, Salmonella Choleraesuis, Bacillus Cereus, Enterococcus Faecalis, Escherichia Coli

Cleaning Instructions:

This product should be cleaned with mild soap and water. Do not use alcohol based cleaners.

ENDURATEX™ and PRODURATECT™ are trademarks of CGPC America Corp. and may not be used without written permission of CGPC America Corp.



ENDURATEX™
We cover the world.

