



Decorative Vinyl & Fabric

DISTRIBUTORS OF LEATHER, VINYL, FABRIC & FOAM

4527 GLENWOOD ROAD • BROOKLYN, NY 11203

Phone: 718 941 3326 • Fax: 718 941 6115

Email: mark@dvcfabric.com



ORIENT

ENDURAPRINT COLLECTION

ENDURATEX™ and PRODURATECT™ are trademarks of CGPC America Corp. and may not be used without written permission of CGPC America Corp.

ORIENT with PRODURATECT™ PLUS
is manufactured to meet the following typical properties:

Width	54"
Roll Size	30 yds.
Nominal Weight	29 oz. per Lin. Yard
Contents	100% PVC
Backing	Polyester/Rayon
Cold Crack	-10°F
Abrasion Resistance	Wyzenbeek (50,000 cycles #10 cotton duck)
	Taber (4.5 ASTM D 3884)
Thickness	1.05 mm
Anti Bacterial/Anti Microbial	Pass
(NYS63/ASTM G-21-90)	

Compatible with commercially available adhesives.

Suggested Applications:

Office Interior, Hospitality, Restaurant, Healthcare,
Gaming, Residential, RV, Marine Interior

Meets flammability requirements*:

Motor Vehicle Safety Standard 302
California Technical Bulletin 117 Section E
New York and New Jersey Port Authority
Federal Aviation Specification 25.853
Boston Fire Department Code
NFPA 260 Class 1
BIFMA Class A
UFAC Class A

*This term and any corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

This product has been treated with anti-bacterial and antimicrobial agents that will provide resistance to the following:
(AATCC Test Method 147-1993)

Bacillus Mycoides
Klebsiella Pneumoniae
Proteus Vulgaris
Staphylococcus Aureus
Salmonella Choleraesuis
Bacillus Cerus
Enterococcus Faecalis
Escherichia Coli

Cleaning instructions: This product should be cleaned with mild soap and water. Do not use alcohol based cleaners.*

