

OVERSHADOW

PURETEX COLLECTION

OVERSHADOW with **PRODURATECT™** topcoat
is manufactured to meet the following typical properties:

Width	54"
Roll Size	30 yds.
Nominal Weight	28 oz. per Lin. Yard
Thickness	0.9 mm
Contents	TPO with PU Topskin
Backing	LK 100% Polyester
Cold Crack	-10°F
UV Stabilized Pigments	300 hours minimum
Abrasion Resistance	Wyzenbeek (100,000 cycles / 10# Cotton Duck)
Class Ratings	ASTM D 3690 - Class A
Mildew Resistance (Front and Back)	Pass
Anti-Bacterial/Anti-Microbial (AATCC 147 / ASTM G-21)	Pass

Compatible with commercially available adhesives.

Suggested Applications:

Hospitality, Healthcare, Restaurant Seating, Lounge Seating, Conference Room, Executive Seating, Office, Residential, RV

Meets flammability requirements*:

Motor Vehicle Safety Standard 302
California Technical Bulletin 117- 2013, Section 1
NFPA 260 Class 1
UFAC Class A
BIFMA Class A

This product has been treated with anti-bacterial and anti-microbial agents that will provide resistance to the following:

(AATCC Test Method 147)

Bacillus Mycoides	Staphylococcus Aureus
Klebsiella Pneumoniae	Salmonella Choleraesuis
Proteus Vugaris	Bacillus Cerus
Enterococcus Faecalis	Escherichia Coli

*This term and any corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Cleaning Instructions:

This product should be cleaned with mild soap and water.
Do not use alcohol based cleaners.

ENDURATEX™ and **PRODURATECT™** are trademarks of CGPC America Corp.
and may not be used without written permission of CGPC America Corp.



CGPC is a certified
ISO/TS 16949:2009
Manufacturer



ENDURATEX™
We cover the world.