

RAPPER XTREME

Premium Vinyl Collection

RAPPER XTREME with PRODURATECT™ is manufactured to meet the following typical properties:

Specifications:

Width 54"
Roll Size 30 yds
Thickness 1.30 mm
Nominal Weight 35 oz. per Lin. yd
Contents PVC
Backing Nylon
Cold Crack -40°F
UV Stabilized Pigments 500 hours minimum
Abrasion Resistance Wyzenbeek:
(100K cycles #10 cotton duck)
Mildew Resistant (ASTM G-21) Pass
Anti-Bacterial/Anti-Microbial (AATCC 147) Pass

Suggested Applications:

Extreme Seating, Automotive, Motorcycle,
Snow Mobile, Jet Ski

Meets Flammability Requirements*:

Motor Vehicle Safety Standard 302
California Technical Bulletin 117-2013, Section 1**
BIFMA, Class A
UFAC, Class 1

*This term and any corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

** This product, when tested with suitable component materials, may comply with California Technical Bulletin 117-2013, Section 1.

This product has been treated with anti-bacterial and anti-microbial agents that will provide resistance to the following:

(AATCC Test Method 147)
Bacillus Mycoides, Klebsiella Pneumoniae, Proteus Vulgaris, Staphylococcus Aureus, Salmonella Choleraesuis, Bacillus Cereus, Enterococcus Faecalis, Escherichia Coli

Oil and Sulfide Resistant

Cleaning Instructions:

This product should be cleaned with mild soap and water. Do not use alcohol based cleaners.

ENDURATEX™ and PRODURATECT™ are trademarks of CGPC America Corp.
and may not be used without written permission of CGPC America Corp.

