

**SONOMA**



LEATHERPLUS

puretex



**SONOMA**

is manufactured to meet the following typical properties:

Width .....	54"
Roll Size .....	25 yds
Thickness .....	1.6 mm
Nominal Weight .....	37 oz. per lin. yard
Contents .....	Upcycled Leather
Cold Crack .....	-10°F
Abrasion Resistance .....	Wyzenbeek (100,000 cycles #10 cotton duck)
UV Stabilized Pigments .....	300 hours minimum

**Suggested Applications:**

Automotive, Contract, Home Furnishings, Hospitality, RV

**Meets flammability requirements\*:**

- California Technical Bulletin 117-2013, Section 1\*\*
- NFPA 260, Class 1
- Motor Vehicle Safety Standard 302
- BIFMA, Class A
- UFAC, Class 1

**Cleaning Instructions:**

This product should be cleaned with mild soap and water.  
Do not use alcohol based cleaners.

\*This term and any corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

\*\*This product when tested with suitable component materials, may comply with California Technical Bulletin 117-2013, Section 1.

ENDURATEX™ is a trademark of CGPC America Corp.  
and may not be used without written permission of CGPC America Corp.



CGPC is a certified  
ISO/TS 16949:2009  
Manufacturer

