

TWILIGHT

PRODURATECT™

TWILIGHT with PRODURATECT™ is manufactured to meet the following typical properties:

TWILIGHT Specifications:

Width	54"
Roll Size	40 yds
Thickness	0.97 mm
Nominal Weight	28 oz. per linear yd
Contents	100% PVC
Backing	Polyester
Cold Crack	-10°F
UV Stabilized Pigments	500 hours minimum
Mildew Resistant (ASTM G-21)	Pass
Anti-Bacterial/Anti-Microbial (AATCC 147).....	Pass
Abrasion Resistance †	Wyzenbeek: (100K cycles #10 cotton duck)

Suggested Applications:

Marine, Spa



This fabric meets or exceeds the ACT performance guidelines. Certification Marks owned by ACT.

† Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

Meets Flammability Requirements*:

IMO FTPC Part 8
California Technical Bulletin 117-2013 Section 1**
Motor Vehicle Safety Standard 302
BIFMA, Class A
UFAC, Class 1
NFPA 260, Class 1

*This term and any corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

** This product, when tested with suitable component materials, may comply with California Technical Bulletin 117-2013, Section 1.

This product has been treated with anti-bacterial and anti-microbial agents that will provide resistance to the following:

(AATCC Test Method 147)
Bacillus Mycoides, Klebsiella Pneumoniae, Proteus Vulgaris, Staphylococcus Aureus, Salmonella Choleraesuis, Bacillus Cereus, Enterococcus Faecalis, Escherichia Coli

Oil and Sulfide Resistant

Cleaning Instructions:

This product should be cleaned with mild soap and water. Do not use alcohol based cleaners.

ENDURATEX™ and PRODURATECT™ are trademarks of CGPC America Corp. and may not be used without written permission of CGPC America Corp.

