

VIRTUE

puretex

PRODURATECT™

VIRTUE with PRODURATECT™ is manufactured to meet the following typical properties:

Specifications:

Width 54"
Roll Size 30 yds.
Thickness 1.0 mm
Nominal Weight 28 oz. per linear yard
Contents 100% PVC
Backing Q1 Polyester
Cold Crack -10°F
UV Stabilized Pigments 500 hours minimum
Abrasion Resistance† Wyzenbeek:
(100K cycles #10 cotton duck)

Suggested Applications:

Hospitality, Healthcare, Restaurant, Lounge, Office,
Corporate, Residential, RV



This fabric meets or exceeds these ACT performance guidelines. Certification Marks owned by ACT.

† Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

Meets Flammability Requirements*:

California Technical Bulletin 117-2013, Section 1**
BIFMA, Class A
UFAC, Class 1
NFPA 260, Class 1

*This term and any corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

** This product, when tested with suitable component materials, may comply with California Technical Bulletin 117-2013, Section 1.

Other Attributes:

Phthalate Free
Flame Retardant Additive Free
Anti-Mildew Additive Free
Anti-Microbial/Anti-Bacterial Additive Free

Cleaning Instructions:

This product should be cleaned with mild soap and water. Do not use alcohol based cleaners.

ENDURATEX™, PRODURATECT™ and puretex are trademarks of CGPC America Corp.
and may not be used without written permission of CGPC America Corp.



ENDURATEX™
We cover the world.

